

Date	04/04/2012 10:15:00
3L ref.	01729, 01730, 01731, 01732 and 01733
Ext. ref.	

Mounting corners (PP)

Upper Foil:

- ◆ 100% acid free, archival safe polypropylene (PP).
- ◆ Thickness: 80 µm (3,15 Mil).
- ◆ Colour: Transparent.

Lower Foil:

- ◆ 100% acid free, archival safe polypropylene (PP).
- ◆ Thickness: 100 µm (3,94 Mil).
- ◆ Colour: Transparent.

- ◆ Adhesive:
 - ◆ Long life adhesive, especially selected for archival application.
 - ◆ 100% water based, High tack pressure sensitive acrylic adhesive.
 - ◆ No stain and no adhesive penetration.
 - ◆ pH-level: Neutral.
 - ◆ Adhesive never touches mounted object.

- ◆ Liner:
 - ◆ One side siliconized, chlorine free (TCF or ECF) kraft paper.
 - ◆ Weight: 120 g/m² (74 lb).
 - ◆ Colour: White.

Temperature:

- ◆ Application temperature: Above +10°C (50°F).
- ◆ Service temperature: -10°C... +60°C (14°F ... 140°F).
- ◆ Long-term heat exposure may result in discoloration of the product.

Testing:

- ◆ pH-value according to ISO 18902. (Internal testing)
- ◆ PAT-test according to ISO 18916.
- ◆ Adhesive aging tests according to ISO 18932. (Internal testing)

General Remark:

- ◆ Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.

It is 3L Consumer Products policy continuously to review our products, and where appropriate implement modifications. We therefore reserve the right to change the specifications of our products and test methods without prior notice. The information on this data sheet is to the best of our knowledge and based on information from our suppliers, in compliance with the truth.